

ROTAJET DEGREASING MACHINERY

Front-Loading spray washer

RJ-FL1500



The front-loading spray washer is a larger system to the Top-Loading counterpart. Because of this, the system is able to degrease and process at much larger volumes.

With the use of high-pressure spray washers and solvents, this system will make easy work of heavily degreasing large parts in addition to greased containers and drums.

Applications


- To wash motor blocks and parts
- To wash any parts at bus, truck, automobile and work machines
- At the workshop which manufacture machining parts and oiled part
- At the firms which engine reconditioning and cylinder head repairing

Features:

- Completely manufactured with stainless steel sheets and components
- Cleaning process timing
- Developed for minimum water, detergent and electric consumption
- Minimum water consumptions by closed water cycling system.
- Heated water (solution) dispensed through high-pressure jet nozzles
- Pneumatic front door movement
- High user safety with pneumatic pistons
- Gear driven rotary table
- Automatic water feeding system

RJ-FL2500





ROTAJET DEGREASING MACHINERY

Front Loading spray washer



Safety Interlocks

Safety interlocks are automatically engaged during the operation of the machine and are only disengaged when the cycle has come to an end and temperatures have returned to a safe level.



Intergrated control measures


We put all the measures in place to so your products are cleaned thoroughly, whilst ensuring the safety of the operator and the longevity of your machine.



3 Standard sizes

To account for our customers varying needs, this machine has 3 standardised sizes fwhich are ideal for the majority of degreasing applications. Find the specs below.

MODEL	RJ-FL1500	RJ-FL1750	RJ-FL2000
Basket diameter	1350	1600	1850
Loading height (mm)	700	800	900
Loading capacity (kg)	650	750	850
Tank capacity (Lt)	300	300	300
Pump Pressure (bar)	2 pieces x 3 bar	2 pieces x 3 bar	2 pieces x 3 bar
Pump quantity and Power	2 pieces x 3 Hp	2 pieces x 3 Hp	2 pieces x 3 Hp
Heater (kW)	15	15	22.5
Electricity (V/phrse/Hz)	220-380-412/ 3-1/ 50-60	220-380-412/ 3-1/ 50-60	220-380-412/ 3-1/ 50-60
Process timer (min)	0-30	0-30	0-30
Working Temp	0-90°C	0-90°C	0-90°C
Rotary Basket	Standard	Standard	Standard
Oil Skimmer	Standard	Standard	Standard
Packing size and weight (mm)	1930x1800x2010 680kg	2250x1950x2200 900kg	2450x2200x2150 900kg



info@rotajet.co.uk
rotajetsystems.co.uk
14 Flanshaw Way, Wakefield
WF2 9LP

FRONT LOADING SPRAY WASHER