

Self-adhesive Waterproof Tape

Product Sheet



DESCRIPTION:	Butyl rubber coated non-woven: rigid in main direction, thin, high tenacity. Butyl rubber tape with release liner with overlaps for easy removal. The non-woven allows a good cementability with common tile adhesives or sealants, structure embossing.		
MATERIAL:	Substrate: Polypropylene non-woven. Coating: Self-adhesive butyl rubber, high elastic, resistant to aging.		
APPLICATION:	Joint sealing tape to be applied with tiles or natural stones for flexible waterproofing of expansion joints. Suitable for indoor application for medium loads of non-pressureizes water (e.g. bathrooms).		
PRODUCT CODE:	311067		
DESCRIPTION:	MARMOX FLEECE 0.6MM X 100MM (10M) O/L X 8		
SEALANT:	0464		
COLOUR:	GREY		
VERSION:	2 (11/07/19)		
STRIP SEALANT TOLERANCES			
	Min	Nominal	Max
STRIP THICKNESS (MM) (INC PAPER & FLEECE)	0.8	0.9	1.0
STRIP WIDTH (MM)	97	100	103
STRIP LENGTH (M)	10	10	10.5
NOMINAL ROLL DIAMETER (MM)	120		
MINIMUM GLOSS LEVEL (%)	80		
SHAPE (FLAT / BEAD / U-SECTION)	FLAT		
STRIP POSITION ON PAPER	CENTRAL		
LAMINATE	MARMOX PP FLEECE 40GSM 103MM		
DRAWING REFERENCE			
<p>The drawing shows a rectangular strip sealant. A horizontal dimension line above the strip is labeled '100mm butyl'. A vertical dimension line to the right of the strip is labeled '0.9mm'. A horizontal dimension line below the strip is labeled '106mm'.</p>			
SETUP ITEMS			
0.6mm butyl, plus 0.1mm paper plus 0.2mm fleece = 0.9mm thickness.			
Ensure that there is not too much tension on the fleece unwind as this can stretch the fleece.			
Line 11: Die = T40, Togum A = Low, Togum B = Low, Conveyor = 11 m/min			
PACKAGING REQUIREMENTS			
PALLET TYPE	AUXI		
ROLLS PER BOX	8		
TOTAL NUMBER OF BOXES PER PALLET	60		
NO LAYERS	5		
BOXES PER LAYER	12		
PALLET DIVIDER CONFIG	DIV1050 UNDER LAYERS 1, 2, 4		

Self-adhesive Waterproof Tape

Product Sheet



Printed Fleece



Label

311067			
MARMOX FLEECE			
THICKNESS DICKE EPAISSEUR	0.6 mm	NUMBER OF ROLLS	8
WIDTH BREITE LARGEUR	100 mm	COLOUR	GREY
LENGTH LANGE LONGUEUR	10 m	BATCH NUMBER	DOM: Expiry:
WO: ??????			

Warranty: 15 years warranty for the guaranteed product qualities

Storage: cool and dry, protect against sunlight, use within 24 months after receipt.

The above technical data represent average values. The technical information and application instructions are based on our experience and present knowledge. However, it is each users own responsibility to make trials with the original substrates in order to verify the suitability of our products for the intended purpose, taking into consideration all application related parameters. Please contact us if you have any further questions.